

VP278QG 1ms Quick Response Time Monitor

Superior Image Quality Meets Classic Elegant Design



■ Key Features ■



Enter a spectacular Full HD world of colors with DisplayPort and HDMI support



1ms response time ensures fluid and clear video playback



Decimating blurry to gain the upper hand in current video games



Flicker-free

To eliminate the disturbing flickers on screen to reduce eye fatigue



Ultra-low Blue Light

You could choose from 4 levels of Ultra-low Blue Light modes for your best viewing and users scenario



Play Like a Pro

Exclusive GamePlus function provides the accurate and perfect gaming experience



Stereo Speakers

Built-in hidden stereo speakers for immersive home theatre experience



Wall Mountable

Compatible with VESA wall-mount standard



Provides variable refresh rates for low latency, stuttering-free and tearing-free while gaming

■ Specification ■

Display	<p>Panel Size : 27-inch (68.6cm) Wide Screen (16:9) True Resolution : 1920 x 1080 Display Colors : 16.7M Brightness : 300 cd/m² (max.) Contrast Ratio (Max.): 1200:1 ASUS Smart Contrast Ratio (ASCR) : 100,000,000:1 Viewing Angle (CR ≥ 10) : 170°(H)/160°(V) Response Time : 1ms (Gray to Gray) Flicker-free : Yes</p>
Video Feature	<p>Trace Free Technology : Yes SplendidPlus Video Intelligence Technology : 8 Modes (Scenery / Standard / sRGB / Theater / Game / Night View / Reading / Darkroom) Skin Tone Selection : 3 modes Color Temperature Selection : 4 modes QuickFit : 7 modes (A4 / B5 / Letter / Alignment Grid 1 / Alignment Grid 1 / Photo 8x10, 5x7 / Photo 4x6, 3x5, 2x2) GamePlus : Yes (Crosshair / Timer / FPS Counter / Display Alignment) HDCP support : Yes Smart View Technology : Yes VividPixel Technology : Yes</p>
Audio Features	2W x 2 stereo, RMS
Convenient Hotkey	<p>Blue Light Filter Brightness Adjustment Input Selection QuickFit</p>
I/O Ports	DisplayPort, HDMI x 2 (DisplayPort and HDMI supports Adaptive-Sync/FreeSync™ 48~75Hz), D-Sub, PC Audio-in
Signal Frequency	<p>Analog Signal Frequency : 24~83 KHz(H)/ 48~75 Hz(V) Digital Signal Frequency : 24~83 KHz(H)/ 48~75 Hz(V)</p>
Power Consumption	<p>Power On (Typical): < 29.1W Power Saving Mode : < 0.5W Power Off Mode : < 0.5W</p>
Mechanical Design	<p>Chassis Colors : Black Tilt : +20°~ -5° VESA Wall Mounting : 100 x 100 mm</p>
Security	Kensington lock
Dimensions	<p>Phys. Dimension with Stand (WxHxD) : 641.4 x 444.5 x 219.4mm Phys. Dimension without Stand (WxHxD) (For VESA Wall Mount): 641.4 x 383.1 x 55 mm Box Dimension (WxHxD) : 704 x 520 x 150mm</p>
Weight	<p>Net Weight (Esti.) : 4.8kg Net Weight without Stand (For VESA Wall Mount) (Esti.): 4.25 kg Gross Weight (Esti.) : 7.2kg</p>
Accessories	Power Cord, VGA Cable, DisplayPort Cable (optional), HDMI Cable (optional), Audio cable, Warranty Card, Quick start guide
Compliance Standard	UL/cUL, CB, CE, ErP, FCC, CCC, CU, RCM, BSMI, VCCI, PSB, RoHS, J-MOSS, MEPS, WEEE, ISO9241-307, PSE, Windows 7 & 8.1 WHQL, Energy Star®, CEL, TUV low blue light filter and flicker free, Adaptive-Sync/FreeSync™

* measuring a screen brightness of 200 nits without audio / USB / Card reader connection

**All specifications are subject to change without notice.